

BLOCO



 IP 66 IK 08 IK 10



MAIN APPLICATIONS



SQUARES & PEDESTRIAN AREAS



CAR PARKS



RAILWAY STATIONS & METROS



ACCENT & ARCHITECTURAL

A versatile tool for marking the way and creating ambiance

The wall recessed BLOCO range is characterised by the wide variety of models, photometric distributions and light sources available.

Rectangular, circular or square, BLOCO perfectly integrates and complements any architectural setting.

The BLOCO floodlight is composed of high-quality materials: a body and cover in painted die-cast aluminium alloy and a glass protector sealed to the cover. A silicone gasket guarantees the IP 66 tightness level.

KEY ADVANTAGES

- > Elegant and robust wall-mounted floodlights for direct or indirect lighting
- > Several models and sizes
- > High-quality and resistant materials
- > Flexible installation
- > High tightness level (IP 66)
- > Easy to install

BLOCO

Typical luminaire output flux (white LEDs)	Up to 250lm
Power consumption	8W
Colour temperature	Neutral white 740
Light distributions	Symmetrical (110°) and asymmetrical (23°-33°) beams
Nominal voltage	220-240V / 50-60Hz
Surge protection	10kV



DIMENSIONS | MOUNTING

BLOCO	Rectangular	BLOCO	Circular direct	BLOCO	Circular indirect	BLOCO	Square
A	294mm 11.6"	A	255mm 10"	A	255mm 10"	A	255mm 10"
B	154mm 6"	B	114mm 4.5"	B	150mm 5.9"	B	108mm 4.2"
C	275mm 10.8"	C	235mm 9.2"	C	235mm 9.2"	C	214mm 8.4"

